

TRAXTER[®]

SOLID BOOM LIFT & TELEHANDLER TYRES



Puncture-Proof
no downtime & repair costs

• **Square Shoulders with Flat Tread Profile**
for smooth ride

• **High Lug to Void Ratio**
for reduced vibration

• **Extra Deep Tread**
for long life

• **Low Profile Section Height**
specially designed for
Aerial Work Platforms

• **Increased Ballast**
for additional safety & stability

• **Supplied as Ready to Fit Tyre & Wheel Assemblies**
for quick & easy onsite fitment

• **Cost-Effective Alternative**
to foam filled tyres

Built Solid

TECHNICAL SPECIFICATIONS

Size	Pattern	Tyre Dimensions						Load Capacity @ 6mph (10km/h)		Equivalent Pneumatic Tyre Size
		Overall Diameter		Section Width		Tread Depth		lbs	kg	
		mm	inch	mm	inch	mm	32nds			
30x10-20	SSK-02	750	29.5	230	9.1	60	75	7920	3600	10-16.5
33x12-20	SSK-02	850	33.5	273	10.5	62	78	10340	4700	12-16.5
36x13-20	SSK-02	915	36.0	305	12.0	75	95	12320	5600	355/55D625, 14-17.5, 12.5/80-18
40x14-24	SSK-02	975	38.4	355	14.0	80	101	13200	6000	15-625, 15-19.5, 385/65D19.5, 18-625
44x15-24	SSK-02	1100	43.3	360	14.2	67	85	12300	5900	385/65D22.5, 15-22.5, 18-19.5
44x15-32	SSK-02	1100	43.3	360	14.2	67	85	12300	5900	
46x18-24	SSK-02	1160	45.7	430	16.9	72	91	16100	7300	445/65D22.5, 445/50D710, 18-22.5, 16/70-24, 405/70-24
46x18-32	SSK-02	1160	45.7	430	16.9	72	91	16100	7300	
50x13-24	SSK-06	1290	1290	320	12.6	104	132	15290	6950	13.00-24, 400/75-28, 19.5L-24 (500/70-24)
50x13-32	SSK-06	1290	50.8	320	12.6	104	132	15290	6950	
13.00-24	SSK-02	1270	50.0	320	12.6	103	130	15290	6950	13.00-24
14.00-24	SSK-02	1340	52.8	350	13.8	112	142	16940	7700	14.00-24

All Tyres conform to ETRTO & T&RA standards



SSK-02



SSK-06



For your requirements please contact -