



Innovation. Passion. Commitment.

SEC SAC



FEATURES

- Stand alone
- 220 V AC operation
- Ceiling mount
- Can independently switch electrical load of up to 400W
- Can switch heavier electrical load by connecting additional relay /s.
- Dual Element Pyro Electric sensor
- Detection angle 360°
- Detection range 6m at 3m height at 25 °C
- Sealed optics
- Sensitivity control
- Lux (Light) level control for operation
- Device on Time control from 10 seconds to 35 minutes
- Re-Trigger switch for extended device on-time
- Permanent device on / Sensor bypass switch
- Sleek ABS housing

TECHNICAL SPECIFICATIONS

ELECTRICAL

Operating voltage: 220 AC (+ 10% -20%)

Power consumption stand by: 0.5 W

Power consumption maximum: 2.5 W

Polarity: Sensitive

ENVIRONMENTAL

Operating temperature: 0 °C to 50 °C

Storage temperature: -10 °C to 60 °C

Operating humidity: 90% non-condensing

Storage humidity: 90% non-condensing

Recommended Installation Environment: Indoor. Residential, light commercial and offices

PHYSICAL

Dimensions: 91mm (dia), 32mm (width)

Net weight : 86 gm

Gross weight with packaging: 112 gm

www.securicoelectronics.com

STAND ALONE PIR MOTION SENSOR

SMART SWITCH