

# MPL-M11

## PUSH AROUND VERTICAL LIFT - SINGLE MAST



### Standard Configuration

- Ground and platform control
- Auxiliary lowering device
- Emergency Stop Button
- Large Gradiometer
- Double Limit Switches
- Screw type outriggers
- Short circuit and leakage protection system

### Optional Configuration

- Lifting power: DC24V power or Manuel
- High grade hydraulic station
- Explosion protection system
- Stainless steel guardrail
- Electric driving power



# MPL-M11

## PUSH AROUND VERTICAL LIFT - SINGLE MAST



Model		MPL-M8	MPL-M10	MPL-M11	MPL-M12
Max. working height		8m	10m	11m	12m
Max. platform height		6m	8m	9m	10m
Platform size		0.60 x 0.55m	0.60 x 0.55m	0.60 x 0.55m	0.60 x 0.55m
Outrigger footprint		1.7 x 1.67m	1.7 x 1.67m	1.93 x 1.77m	1.93 x 1.77m
Overall length (Stowed)		1.34m	1.34m	1.45m	1.45m
Overall width (Stowed)		0.85m	0.85m	0.85m	0.85m
Overall height (Stowed)		2m	2m	2m	2m
Platform capacity (SWL)		130kg	130kg	130kg	130kg
Ground clearance		0.05m	0.05m	0.05m	0.05m
Weight		370kg	390kg	400kg	420kg
Max. no of person		1	1	1	1
Lifting motor (AC)	Power source	0.75kW	0.75kW	0.75kW	1.1kW
Optional configuration	Lifting motor (DC)	24V/80Ah	24V/80Ah	24V/80Ah	24V/80Ah
		0.80kW	0.80kW	0.80kW	0.80kW
	Charger	24V/15A	24V/15A	24V/15A	24V/15A



Double Limit Switches




Electric Cabinet



Fixture for Platform Guardrail



Gradienter



Limiting Screw for Outriggers

