

A **TATA** Product

**VOLTAS**

# PROFIT FROM COOLING



**COMMERCIAL REFRIGERATION RANGE 2020**



Eco friendly Gas Refrigerant



UV Grade plastic for long-lasting appearance



Spring loaded hinges for effortless usage

-25° C  
0 to +10° C  
Temperature Range



Energy efficient compressor



Anti-condensate pre-cast body



Compact design



Low E (Emission) glass



Rugged and Heavy-duty shelves



Dual Temperature Freezing/Cooling



AUTO Auto defrost



LED light



Caster wheels for easy mobility



Stucco Aluminium/Metal Inner Liner for improved hygiene



Soft aesthetic design



Single-Mould Construction



Tropicalized machines



Up to 40% electricity saving



Longer cooling retention.



Soften handles for safer operations



Electronic controller



Self closing door



Safety compliant









# HARD TOP CONVERTIBLE

METAL TOP



A marvel of cutting-edge technology in a corrosion-resistant durable body. Store beverages, dairy products, frozen food and ice-cream together, at their ideal temperature. For innovative features like tropicalized compressor, multi-usage capabilities and cooking retention components, look no further. The storage system boasts of eco-friendly refrigerants which contribute to reduced global warming. The Hard Top Convertibles are aesthetically crafted, and built to last for years to come.



-  Soft aesthetic design
-  Caster wheels for easy mobility
-  Energy efficient compressor
-  Upto 40% electricity saving
-  Stucco Aluminium/Metal Inner Liner for improved hygiene
-  UV Grade plastic for long-lasting appearance
-  Door lock for restricted accessibility
-  Anti-corrosive pre-coated body
-  Spring loaded hinges for effortless usage
-  Eco Friendly Refrigerant
-  Dual Temperature Freezing/Defrosting
-  Longer Cooling Retention
-  Safety Compliant
-  Sunken handle for safer operation
-  Tropicalized machines
-  Compact design

## TECHNICAL SPECIFICATIONS - CONVERTIBLES

Model No.	110 SD HT GREY CONVERTIBLE	150 SD HT GREY CONVERTIBLE	210 SD HT Convertible / 205 SD HT CONVERTIBLE PCM	320 DD HT Convertible PCM / 320 DD P HT CONVERTIBLE PCM	405 DD HT CONVERTIBLE	500 DD HT CONVERTIBLE	800 DD HT CONVERTIBLE
Product Dimension (WxDxH) in mm	620x550x830	735x575x826	925x575x826 / 834x665x830	1110x635x826 / 1180x665x830	1450x665x830	1680x665x830	1945X757X880
Gross Volume (In Ltr.)	110	150	210 / 205	320	405	500	800
No. Of Doors	1	1	1	2	2	2	2
Refrigerant Type	R-600a	R-600a	R-600a / R-134a	R-600a / R-134a	R-134a	R-134a	R-290a
Basket	1	1	1	1	2	2	1
Temperature Range	<-18°C(Freezer), 0° to 7°C(Cooler)	<-18°C(Freezer), 0° to 7°C(Cooler)	<-18°C(Freezer), 0° to 7°C(Cooler)	<-18°C(Freezer), 0° to 7°C(Cooler)	<-18°C(Freezer), 0° to 7°C(Cooler)	<-18°C(Freezer), 0° to 7°C(Cooler)	<-18°C(Freezer), 0° to 7°C(Cooler)
PUF Thickness	70mm	70mm	65 mm / 60mm	65 mm / 60 MM	60mm	60mm	70mm



# COMBO COOLERS



Enjoy the dual functionality of a cooler and a freezer. The cooler compartment can be used for storing cold beverages. The freezer, for storing ice-cream and frozen foods. The coolers come with robust construction for heavy duty use. Tropical compressor in Combo Coolers ensures high performance freezing even in higher ambient temperatures of the Indian summer.



-  Soft aesthetic design
-  Caster wheels for easy mobility
-  Energy efficient compressor
-  Up to 40% electricity saving
-  Stucco Aluminium/Metal liner for improved hygiene
-  UV Grade plastic for long-lasting appearance
-  Door lock for restricted accessibility
-  Anti-corrosive pre-coated body
-  Spring loaded hinges for effortless usage
-  Eco Friendly Gas Refrigerant
-  Compact design
-  Safety Compliant
-  Tropicalized machines
-  Dual Temperature Freezing/Cooling

## TECHNICAL SPECIFICATIONS - COMBO COOLERS

Model No.	300 CB FC HT	400 CB FC HT
Product Dimension (WxDxH) in mm	1329X575X832 mm	1275X740X825 mm
Gross Liters (F/R)	300	400
No. Of doors	2	2
Refrigerant Type	R600a	R290a
Basket	1	1
Temperature Range	<-18°C(Freezer), 0° to 7°C(Cooler)	<-18°C(Freezer), 0° to 7°C(Cooler)
PUF thickness	65 mm	65 mm



# FLAT GLASS TOP FREEZERS

GLASS TOP



Frozen foods and ice creams find a robust and reliable home in the Flat Glass Top Freezers. Built sturdy for heavy use. Freezers are tropicalised for better cooling at higher temperatures. Low-emissive glass for better visibility and insulation. Choose from attractive colours which showcase the products more prominently. Also available with an optional in-built stabilizer and LED lights.



## TECHNICAL SPECIFICATIONS - FLAT GLASS TOP FREEZERS

Model No.	50 GSL	120 GSL	205 GSL / 210 FGSL	320 GSL	405 GSL
Product Dimension (WxDxH) in mm	620X540X500	685x535x815	*848X635X815/ 930x545x784	1195X635X815	1465X635X815
Gross Volume (In Ltr.)	50	120	205 / 210	320	405
No. Of Doors	2	2	2	2	2
Refrigerant Type	R-134a	R-134a	R-134a /R600a	R-134a	R-134a
Basket	1	1	1	1	2
Temperature Range	<-18°C	<-18°C	<-18°C	<-18°C	<-18°C
PUF Thickness	60mm	60mm	60mm / 65mm	60mm	60mm





# CURVED GLASS TOP FREEZERS

GLASS TOP



Showcase in style. Ideal for the storage and display of ice-creams and frozen foods. Castor wheels at the bottom offer easy mobility.



## TECHNICAL SPECIFICATIONS - CURVED GLASS TOP FREEZERS

Model Name	Curved Glass Top Flat 200	220 CF Curved Glass Top-Red / White / LP	300 CF Curved Glass Top-Red / White / LP	Curved Glass Top Flat 350	400 CF Curved Glass Top- Red / White / LP / Curved Glass Top Flat 350	450 CF Curved Glass Top-Red / White / LP	550 CF Curved Glass Top-Red / White / LP
Product Dimension (Wx - DxH) in mm	610x553x900	820x690x900	1020x690x905	1034x653x900	1220x690x905 / 1234x653x900	1420x690x900	1620x690x900
Gross Volume (In Ltr.)	156	220	300	336	400	450	550
No. Of Doors	2	2	2	2	2	2	2
Refrigerant Type	R 290a	R134a	R134a	R 290a	R134a / R290 a	R134a	R134a
Basket/Shelves	0	2pcs/wire	2pcs/wire	0	2 / 0	2pcs/wire	2pcs/wire
Temperature Range	<-18°C	<-18°C	<-18°C	<-18°C	<-18°C	<-18°C	<-18°C
PUF Thickness	70 mm	65mm	65mm	70 mm	65 mm / 70 mm	65 mm	65 mm



# CHOCOLATE COOLERS

GLASS TOP



What could make chocolates look even better? The Chocolate Coolers. Combining sturdy with style, their polished design showcases the chocolates in the best way possible. The coolers are tropicalised to maintain the optimum temperature under high ambient temperatures. The shelves are customisable. It even comes with LED lights to shine the spotlight on your star products.



## TECHNICAL SPECIFICATIONS -CHOCOLATE COOLERS

Model No.	CT 15	CT 33
Product Dimension(mm)	440X550X450	600X51X480
Gross Volume (In Ltr.)	15	30
No.Of Glass Doors	1	1
Refrigerant Type	R134 a	R134 a
Basket/Shelves	Yes Customized	Yes Customized
Temperature Range	+18 to +22°C	+18 to +22°C
PUF Thickness	45 mm	45 mm



# VISI COOLERS

VISI COOLER



Form meets function in this stylish merchandiser. The Visi Coolers are especially designed to cool uniformly as well as showcase the products inside. Ideal for storing beverages and dairy products for a longer time at desired temperatures. The low emissivity glass is there for more than just good looks. It also restricts the loss of cooling. The coolers are tropicalized for cooling in high temperatures and designed for faster pull down time. They also come with an option for in-built stabilizer and LED lights. These compact storage solutions are a perfect match for commercial cooling purposes.



## TECHNICAL SPECIFICATIONS - VISI COOLERS

Model No.	VC 70	VC 120	VC 220/ VC 220 FLGS	VC 320 / VC 320 FLGS	VC 425
Product Dimension	455 x 515 x 720	475 x 585 x 1060	535 x 670 x 1390	560 x 705x 1680	650 x 725 x 1910
Gross Volume (In Ltr.)	70	120	220	320	425
No.Of Doors	1	1	1	1	1
Refrigerant Type	R-134a	R-134a	R-134a	R-134a	R-134a
Basket/Shelves	2	2	3	4	4
Temperature Range	0°C to 7°C	0°C to 7°C	0°C to 7°C	0°C to 7°C	0°C to 7°C
PUF Thickness	45mm	45mm	45mm	45mm	45mm



# FREEZER ON WHEELS



Store your ice cream for longer. Move it with the utmost ease with Freezer on Wheels. These freezers come with sturdy anti-corrosive plastic mould bodies that offer a longer shelf-life to your products. Tropicalized compressors provide better cooling. Attractive colour options offer better product display. A sturdy design allows better temperature retention. Sturdy wheels allow ease of movement.



Safety Compliant



Easy Accessibility



Single Mould Construction



Anti-corrosive pre-coated body



Longer Cooling Retention



Tropicalized machines



Compact design



Energy efficient compressor

## TECHNICAL SPECIFICATIONS -FREEZER ON WHEELS

Model No.	VFOWE HT 100 SD	VFOWE HT 135 SD	VFOWE HT 135 DD	VFOWE HT 200 DD
Product Dimension(mm)	940 X 635 X695mm	940 X 635 X795mm	940 X 635 X795mm	1000 X 650 X 913mm
Gross Volume (In Ltr.)	115	135	135	200
No.Of Doors	1	1	2	2
Refrigerant Type	R404a	R404a	R404a	R404a
Temperature Range	< -18 to -30°C	< -18 to -30°C	< -18 to -30°C	< -18 to -30°C
PUF Thickness	70mm	70mm	70mm	70mm





# VERTICAL FREEZERS

METAL TOP



Enjoy more product visibility for your frozen foods, with a smaller footprint. The Vertical Freezers come with LED lights, lit canopy display, adjustable shelves, moving wheels and low emission glass which prevents moisture on glass door. Your products also enjoy a longer shelf life with temperature control options, tropicalized compressor, robust design and eco-friendly refrigerant. Better visibility leads to better profits.



-   
Soft aesthetic design
-   
Castor wheels for easy mobility
-   
Self closing door with lock
-   
Up to 40% electricity saving
-   
Rugged and heavy-duty shelves
-   
UV Grade plastic for long-lasting appearance
-   
Auto Defrost
-   
Anti-corrosive pre-coated body
-   
Longer Cooling Retention
-   
Low emissivity glass to avoid cooling loss
-   
Compact design
-   
Energy efficient compressor
-   
Safety Compliant
-   
Semi Tropicalized Machine
-   
Stucco Aluminium inner liner for improved hygiene
-   
LED Light
-   
Electronic controller

## TECHNICAL SPECIFICATIONS - VERTICAL FREEZERS

Model No.	1000 Ltr.SD Upright Freezer	500 Ltr.SD Upright Freezer
Product Dimension(mm)	1998x1200x690	1998X600X690
Gross Volume (In Ltr.)	1000	500
No.Of Doors	2	1
Refrigerant Type	R404a	R404a
Basket/Shelves	10 shelves	5
Temperature Range	< -23°C	< -23°C
PUF Thickness	70 mm	70 mm

# WATER COOLERS

STAINLESS  
STEEL TOP



Quench your thirst for chilled water with Voltas Water Coolers. A Stainless Steel 340 and reciprocating tropicalized compressor, housed in a vertical design for near-instant optimum cooling. Never run out of cool water again.



Soft aesthetic design



Logger Cooling Efficiency



Compact design



Safety Compliant



Upto 40% electricity saving



Eco friendly Refrigerant



Anti-corrosive pre-coated body



Energy efficient compressor



Tropicalized machines



In-situ puf insulation

## TECHNICAL SPECIFICATIONS - WATER COOLER

PARAMETERS DESCRIPTION	20/20 PSS & FSS	20/40 PSS & FSS	40/40 PSS & FSS	40/80 PSS & FSS	60/80 PSS & FSS	60/120 PSS & FSS	150/150 PSS & FSS-RECIP.COMP	150/150 PSS & FSS-ROTARY COMP	150/300 PSS & FSS
STORAGE CAPACITY (Ltrs)	20	40	40	80	80	120	150	150	300
COOLING CAPACITY (Ltrs/Hour)	20	20	40	40	60	60	150	150	150
CABINET MATERIAL	G.I POWDER COATED / SS	G.I POWDER COATED / SS	G.I POWDER COATED / SS	G.I POWDER COATED / SS	G.I POWDER COATED / SS	G.I POWDER COATED / SS	G.I POWDER COATED / SS	G.I POWDER COATED / SS	G.I POWDER COATED / SS
TANK	Stainless Steel								
NUMBER OF FUCETS	1	1	2	2	2	2	2	2	5 (3+2 OPTIONAL)
REFRIGERANT	R-134 a	R-134 a	R-134a	R-134a	R-134a	R-134a	R-22 / R-134a	R-22	R-134a
OVER ALL PRODUCT DIMENSIONS WITH TROUGH (WxDxH) mm	364 X 505 X 1117	461 X 582 X 1217	461 X 582 X 1217	461 X 582 X 1441	461 X 582 X 1441	564 X 705 X 1397	564 X 705 X 1521	564 X 705 X 1521	1250x890x1500
Temperature Range	10 TO 25 °C	10 TO 25 °C	10 TO 25 °C	10 TO 25 °C	10 TO 25 °C	10 TO 25 °C	10 TO 25 °C	10 TO 25 °C	10 TO 25 °C
Compressor	Reciprocating Compressor	Reciprocating Compressor	Reciprocating Compressor	Reciprocating Compressor	Reciprocating Compressor	Reciprocating Compressor	Reciprocating Compressor	Rotary	Reciprocating Compressor



# WATER DISPENSERS



Not just hot and cold but also pure and safe. Presenting the new range of water dispensers with RO purifiers. The new range does more than let you choose between Hot, Normal & Cold water. It also puts every drop through a 4-stage filtration process. A Sediment filter, Pre-carbon filter, RO membrane and Post-carbon filter. Water Dispensers are the smart choice for every office and home.



Soft aesthetic design



UV Grade plastic for long-lasting appearance



Eco Intensity Gas Refrigerant



Energy efficient compressor



Safety Compliant



Tropicalized machines



Compact design



Anti-corrosive pre-coated body

## TECHNICAL SPECIFICATIONS - WATER DISPENSERS

Model	Minimagic Pure T	Minimagic Pure R	Minimagic Pure F	Minimagic Pearl FB	Minimagic Pearl FB	Minimagic Pearl R	Minimagic Pure FS	Minimagic Super T	Minimagic Super R
<b>Unit Specification</b>									
Type	Table Top	Floor Mounted	Floor Mounted	Floor Mounted	Floor Mounted	Floor Mounted	Floor Mounted	Table Top	Floor Mounted
Cabinet Type	NA	Cooling Cabinet	only storage cabinet	Cooling Cabinet	NA	Cooling Cabinet	NA	NA	Cooling Cabinet
No. of Faucets	3 Nos.	3 Nos.	3 Nos.	3 Nos.	3 Nos.	3 Nos.	3 Nos.	3	3
Cold Water Storage Capacity	3.2 Ltrs	3.2 Ltrs	3.2 Ltrs	3.2 Ltrs	3.2 Ltrs	3.2 Ltrs	3.2 Ltrs	3.2	3.2
Cooling Capacity	3 Ltrs / Hr	2.5 Ltrs / Hr	3Ltrs / Hr	2.5 Ltrs / Hr	3 Ltrs / Hr	2.5 Ltrs / Hr	3Ltrs / Hr	3	2.5
Hot Water Storage Capacity	0.9Ltrs	0.9Ltrs	0.9Ltrs	0.9Ltrs	0.9Ltrs	0.9Ltrs	0.9Ltrs	0.9Ltrs	0.9Ltrs
Line Dimension (W X D X H) in mm	310 x 345 x 490	310 x 345 x 940	310 x 345 x 940	310 x 345 x 940	310 x 345 x 490	310 x 345 x 940	319 x 345 x 940	325x380x555	325x380x1000
Weight in Kg.	12.8	18.2	16.7	18.2	12.8	18.2	16.7	11.4	16.5
Refrigerant	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)
Cabinet Capacity/Refrigerator Capacity	NA	20 Ltrs	20 Ltrs	20 Ltrs	NA	20 Ltrs	NA	N/A	19/20
Cooling Cabinet Temperature	NA	+12°C	NA	+12°C	NA	+12°C	NA	NA	+12°C
Function	Hot, Normal & Cold	Hot, Normal & Cold	Hot, Normal & Cold	Hot, Normal & Cold	Hot, Normal & Cold	Hot, Normal & Cold	Hot, Normal & Cold	Hot, Normal & Cold	Hot, Normal & Cold
Display	LED Indicator	LED Indicators	LED Indicators	LED Indicators	LED Indicators	LED Indicators	LED Indicators	LED Indicator	LED Indicators
Hot Water Dispensing Lock	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
RO TDS	NA	NA	NA	NA	NA	NA	NA	NA	NA

Model	Minimagic Super R	Minimagic Plus T	Minimagic Plus R	Minimagic Plus F	Minimagic Wave T	Minimagic Wave R	Minimagic Wave F	Minimagic FM BL 3.0 Pure	Voltas Minimagic WDR FM 3.0 Pure RB	Voltas Minimagic WDR TT 3.0 Pure RB
<b>Unit Specification</b>										
Type	Floor Mounted	Table Top	Floor Mounted	Floor Mounted	Floor Mounted	Floor Mounted	Floor Mounted	Floor Mounted	Floor Mounted	Table Top
Cabinet Type	only storage cabinet	NA	Cooling Cabinet	only storage cabinet	NA	Cooling Cabinet	only storage cabinet	only storage cabinet	RO Ki cabinet	Not Applicable
No. of Faucets	3	3	3	3	3	3	3	3	3	2
Cold Water Storage Capacity	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	8	3.2
Cooling Capacity	3	3	2.5	3	3	2.5	3	3	6	3
Hot Water Storage Capacity	0.9Ltrs	0.9Ltrs	0.9Ltrs	0.9Ltrs	0.9Ltrs	0.9Ltrs	0.9Ltrs	0.9Ltrs	0.9Ltrs	0.9Ltrs
Line Dimension (W X D X H) in mm	325x380x1000	325x400x750	325x380x1000	325x380x1000	310x345x940	310x345x940	310x345x940	310x345x940	550x380x980	330x270x950
Weight in Kg.	16.3	11.4	16.7	16.3	11.4	16.65	15.5	15.5	25.7	18.2
Refrigerant	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)
Cabinet Capacity/Refrigerator Capacity	19/20	NA	19/20	19/20	NA	19/20	19/20	NA	NA	NA
Cooling Cabinet Temperature	NA	NA	+12°C	NA	NA	+12°C	NA	NA	NA	NA
Function	Hot, Normal & Cold	Hot, Normal & Cold	Hot, Normal & Cold	Hot, Normal & Cold	Hot, Normal & Cold	Hot, Normal & Cold	Hot, Normal & Cold	Hot, Normal & Cold	Hot, Normal & Cold	Hot, Normal & Cold
Display	LED Indicators	LED Indicators	LED Indicators	LED Indicators	LED Indicators	LED Indicators	LED Indicators	LED Indicators	LED Indicators	LED Indicators
Hot Water Dispensing Lock	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
RO TDS	NA	NA	NA	NA	NA	NA	NA	NA	less than 150ppm	less than 150ppm



A **TATA** Product

**VOLTAS**



# **VOLTAS** | COMMERCIAL REFRIGERATION

Voltas 24x7 Customer Service - 1860 599 4555, 9650694555.  
For product registration SMS <WTA> to 9289525321

Visit us at [www.myvoltas.com](http://www.myvoltas.com). To locate your nearest store,  
log on to: [www.myvoltas.com/store-locator](http://www.myvoltas.com/store-locator)

Follow us at [f My Voltas](#) [t My Voltas](#) [i My Voltas](#)  
[in Voltas Limited](#) [v My Voltas](#)

CORPORATE HEAD OFFICE: Voltas Limited, Voltas House A, Dr. Babasaheb Ambedkar Road, Chinchpokli, Mumbai - 400033, Phone: 022-66656666. DELHI: Voltas Limited, A-43, Mohan Co-operative Industrial Estate, Mathura Road, New Delhi - 110044, Phone: 011-66505550

Voltas Ltd. adheres to the E-Waste (Management & handling) Rules 2011 notified by the Ministry of Environment and Forests, Government of India. This product has been manufactured with high quality parts and materials which can be reused and are suitable for recycling. Do not dispose of the waste product with normal domestic and other wastes at the end of its service life. For more information on Voltas E-Waste and exchange policy please contact Voltas 24x7 Customer Service - 1860 599 4555, 9650694555.

\*Features are available in select models only. T&C Apply.

\*As a continuing policy of product innovation at Voltas, the design and specifications are subjected to change without prior notice.